



# DATA SHEET

## PRESSURE SENSITIVE TAPES Tape Products Engineered to your Specifications

PRODUCT: 10181-L Tape

CONSTRUCTION: 0.00035 aluminum foil  
0.00048" polyester film  
0.0025" acrylic pressure sensitive adhesive  
90# tight release liner

<u>PROPERTY</u>	<u>VALUE</u>	<u>TEST METHOD</u>
Thickness:	0.0038" +/- 10%	ASTM-D-3651-83
Peel Strength:	45 oz./inch of width	ASTM-D-1000
Tensile Strength:	6,000 P.S.I.	ASTM-D-882
Elongation at Break:	90%	ASTM-D-882
Color:	Silver	
Shelf Life:	1 year when stored under conditions of 70 degrees F. (21 degrees C.) and 50% R.H.	

P/N 10181

Rev 2: 02/21/07

*Values are not intended for Engineering Specifications. Before using, user shall determine the suitability of the product for his intended use, and user assumes all risk and liability whatsoever in connection therewith.  
Seller assumes no liability beyond the replacement value of material.*

•Manufacturers of Flexible Laminated and Coated Products. Fabrics.

•Electrical and Electronic Shielding and insulation Composites.

•Specialty Pressure Sensitive Tapes- Laminates-Films, Foils, Papers,