



DATA SHEET

PRESSURE SENSITIVE TAPES

Tape Products Engineered to your Specifications

PRODUCT:	101 Tape	
CONSTRUCTION:	Backing: 0.00092 inch Polyester Film Adhesive: Acrylic Interliner: Available	
APPLICATION:	Particularly useful in applications where the tape is exposed to oils and solvents. Over laminating film for labels.	
FEATURES / BENEFITS:	<p>Exceptional resistance to oils and solvents is useful for protecting labels in transportation and industrial applications.</p> <p>Clear tape and adhesive are advantages when printed material needs to be protected.</p> <p>Excellent balance of adhesion properties for secure binding and wrapping applications.</p> <p>Extensible film for conformability on both irregular and curved surfaces.</p> <p>Available lined version can be printed and die cut.</p>	
SPECIFICATION:	Meets Federal Specification L-T-100 Type I	
INSULATION CLASS:	130 degrees C.	
<u>PROPERTY</u>	<u>VALUE</u>	<u>TEST METHOD</u>
Thickness:	0.002 inch +/- 10%	ASTM-D-3652
Peel Strength:	20 oz./inch of width	ASTM-D-1000
Breaking Strength:	25 lbs./inch of width	ASTM-D-1000
Elongation at Break:	100%	ASTM-D-1000
Color:	Clear	
Shelf Life:	1 year when stored under conditions of 70 degrees F. (21 degrees C.) and 50% R.H.	

P/N 1144

Rev. 2: 04/27/07

*Values are not intended for Engineering Specifications. Before using, user shall determine the suitability of the product for his intended use, and user assumes all risk and liability whatsoever in connection therewith.
Seller assumes no liability beyond the replacement value of material.*

•Manufacturers of Flexible Laminated and Coated Products. Fabrics.

•Electrical and Electronic Shielding and insulation Composites.

•Specialty Pressure Sensitive Tapes- Laminates-Films, Foils, Papers,