



DATA SHEET

PRESSURE SENSITIVE TAPES Tape Products Engineered to your Specifications

PRODUCT: 396L TAPE

CONSTRUCTION: 0.001 inch Aluminum Foil
Glass Cloth
High Temperature, High Tack Acrylic Adhesive
90# release liner

APPLICATION: Heat Reflective:
Shield for wires, cables, instruments in
automotive, aircraft and aerospace applications.

<u>PROPERTY</u>	<u>VALUE</u>	<u>TEST METHOD</u>
Thickness:	0.0045 inch +/- 10%	ASTM-D-3652
Peel Strength:	50 oz./inch of width	ASTM-D-1000
Breaking Strength:	90 lbs./inch of width	ASTM-D-1000
Elongation at Break:	5%	ASTM-D-1000
Color:	Silver	
Service Temperature:	-40 to 300 degrees F. (Maximum in-service temperature range may be greater)	
Shelf Life:	1 year when stored under conditions of 70 degrees F. (21 degrees C.) and 50% R.H.	

P/N 15547

date: 01/05/07

*Values are not intended for Engineering Specifications. Before using, user shall determine the suitability of the product for his intended use, and user assumes all risk and liability whatsoever in connection therewith.
Seller assumes no liability beyond the replacement value of material.*

•Manufacturers of Flexible
Laminated and Coated Products.
Fabrics.

•Electrical and Electronic Shielding
and insulation Composites.

•Specialty Pressure Sensitive Tapes-
Laminates-Films, Foils, Papers,