



DATA SHEET

PRESSURE SENSITIVE TAPES

Tape Products Engineered to your Specifications

PRODUCT: LT-17 M

CONSTRUCTION: Scrim reinforced, metalized polyether ether ketone backing, coated with a high performance acrylic PS adhesive, and protected with a paper liner.

FEATURES: Strong, yet light weight.
Excellent adhesion to covering films, as well as to fibrous insulation materials.

APPLICATION: Used for making, installing and repairing aircraft thermal/acoustic insulation blankets.

Meets FAR 25.856(a), FAR 25.853, FAR 25.855

| <u>PROPERTY</u> | <u>ENGLISH</u> | <u>METRIC</u> | <u>TEST METHOD</u> |
|---------------------------------|-------------------------|--------------------|--------------------|
| Color: | Metallic | | |
| Peel Strength: (24 hr dwell) | SS: 32oz in | >9N/25.4mm | PSTC 101 |
| Breaking Strength: | 13 lb min. | >60N min. | Fed Std 191 TM5100 |
| Weight w/o liner: | 2.8 oz sq yd + - 0.2 | 95 g/m2 + - 6.8 | LTM 25A |

Shelf life: 2 years from date of manufacture. Recommended conditions, store in original container @ 70f (21C) and 50% RH

LTM: Lamart test methods available on request

P/N 16316

date: 09/26/08

Values are not intended for Engineering Specifications. Before using, user shall determine the suitability of the product for his intended use, and user assumes all risk and liability whatsoever in connection therewith. Seller assumes no liability beyond the replacement value of material.

•Manufacturers of Flexible Laminated and Coated Products. Fabrics.

•Electrical and Electronic Shielding and insulation Composites.

•Specialty Pressure Sensitive Tapes- Laminates-Films, Foils, Papers,