



LAMART CORPORATION

Flexible Laminate Solutions

Technical Data

www.lamartcorp.com

800-LAMART9

973-772-6262

PRODUCT ID: LT-18 MD

DESCRIPTION: PRESSURE SENSITIVE TAPES
Tape Products Engineered to your Specifications

CONSTRUCTION: Scrim reinforced, metallized, delustered polyether ether ketone backing, coated with a high performance acrylic PS adhesive and protected with a paper liner.

BENEFITS: -Strong, yet light weight.
-Excellent adhesion to covering films, as well as to fibrous insulation materials.

APPLICATION: Used for making, installing and repairing aircraft thermal/acoustic insulation blankets.

Meets FAR 25.856(a), FAR 25.853, FAR 25.855

<u>PROPERTY</u>	<u>ENGLISH</u>	<u>METRIC</u>	<u>TEST METHOD</u>
Color:	Metallic		
Peel Strength: (24 hr dwell)	SS: 64oz in	17.8N/25.4mm	PSTC 101
Breaking Strength:	10 lb min.	44N min.	Fed Std 191 TM5100
Weight w/o liner:	2.2 oz sq yd + - 0.2	74.6 g/m2 + - 6.8	LTM 25A
Shelf life:	2 years from date of manufacture. Recommended conditions, store in original container @ 70f (21C) and 50% RH		

LTM: Lamart test methods available on request

P/N 16372

Date: 05/09/08

Values are not intended for Engineering Specifications. Before using, user shall determine the suitability of the product for his intended use, and user assumes all risk and liability whatsoever in connection therewith. Seller assumes no liability beyond the replacement value of material.

Automotive . Aerospace . Electronics . Industrial . Medical . Printing and Graphics