



LAMART CORPORATION

Flexible Laminate Solutions

Technical Data

www.lamartcorp.com

800-LAMART9

973-772-6262

PRODUCT ID: 326 HARNESS WRAP TAPE

DESCRIPTION: **PRESSURE SENSITIVE PRODUCTS**
Products Engineered to your Specifications

CONSTRUCTION: Backing: 0.00035" aluminum
0.00092" polyester
Adhesive: Acrylic
Interliner: Available

APPLICATION: High temperature reflective tape designed for under hood wire harness wrap for cars, trucks or anywhere protection from radiant heat is required.

BENEFITS: -Exposed aluminum foil offers a mirror like surface that is an excellent reflector of radiant heat.
-Aggressive acrylic PS adhesive is designed to offer excellent quick stick and ultimate adhesion.
-Polyester layer gives the tape extra strength at an economical price.

<u>PROPERTY</u>	<u>VALUE</u>	<u>TEST METHOD</u>
Thickness:	0.0018inch +/- 10%	ASTM-D-3652
Peel Strength:	44 oz/inch of width	ASTM-D-1000
Breaking Strength:	25 lbs/inch of width	ASTM-D-1000
Elongation at Break:	130 %	ASTM-D-1000
Color:	Silver	
Surface Resistivity:	20 milliohms/sq in	MIL-STD 202 Method 303
Shelf Life:	1 year when stored under conditions of 70 degrees F. (21 degrees C.) and 50% R.H.	

P/N 3385

Date: (Rev.2) 04/26/07

Values are not intended for Engineering Specifications. Before using, user shall determine the suitability of the product for his intended use, and user assumes all risk and liability whatsoever in connection therewith. Seller assumes no liability beyond the replacement value of material.

Automotive . Aerospace . Electronics . Industrial . Medical . Printing and Graphics