



DATA SHEET

ELECTROSHIELD

Laminates and Coated Products Engineered
to Solve EMI/RFI Shielding Problems

PRODUCT: C-35-NPS

CONSTRUCTION: .0014" ED Copper
.002" Polyester Film

APPLICATION: Electrical and Electromagnetic
Shielding and Compatible with
Copper Braids and Copper Conductors

<u>PROPERTY</u>	<u>VALUE</u>	<u>TEST METHOD</u>
Thickness:	.0035" +/- 10%	ASTM-D-374
Breaking Strength:	78 lbs/in of width	ASTM D-882
% Elongation at Break:	10 %	ASTM D-882
Color:	Copper	
Weight per Sq Yd:	10.65 oz/sq yd	
Yield:	1.5 sq yds/lb	
Shelf Life:	1 year when stored under conditions of 70 degrees F. (21 degrees C.) and 50% R.H.	

P/N 450

date 12/22/97

*Values are not intended for Engineering Specifications. Before using, user shall determine the suitability of the product for his intended use, and user assumes all risk and liability whatsoever in connection therewith.
Seller assumes no liability beyond the replacement value of material.*

•Manufacturers of Flexible
Laminated and Coated Products.
Fabrics.

•Electrical and Electronic Shielding
and insulation Composites.

•Specialty Pressure Sensitive Tapes-
Laminates-Films, Foils, Papers,