



# DATA SHEET

## PRESSURE SENSITIVE TAPES

Tape Products Engineered to your Specifications

PRODUCT: 108 TAPE

CONSTRUCTION: Backing: 0.005" Polyester Film  
Adhesive: Acrylic  
Interliner: Available

APPLICATION: Bundling or binding applications where extra strength and puncture resistance are required.

FEATURES / BENEFITS: Strong, durable film offers superior tensile strength and puncture resistance.

Aggressive acrylic PS adhesive is designed to offer excellent quick stick and ultimate adhesion.

<u>PROPERTY</u>	<u>VALUE</u>	<u>TEST METHOD</u>
Thickness:	.006 inch +/- 10%	ASTM-D-3652
Peel Strength:	32 oz./inch of width	ASTM-D-1000
Breaking Strength:	100 lbs./inch of width	ASTM-D-1000
Elongation at Break:	150%	ASTM-D-1000
Color:	Clear	
Shelf Life:	1 year when stored under conditions of 70 degrees F. (21 degrees C.) and 50% R.H.	

P/N 462

Rev. 1: 04/27/07

*Values are not intended for Engineering Specifications. Before using, user shall determine the suitability of the product for his intended use, and user assumes all risk and liability whatsoever in connection therewith.*

*Seller assumes no liability beyond the replacement value of material.*

•Manufacturers of Flexible Laminated and Coated Products. Fabrics.

•Electrical and Electronic Shielding and insulation Composites.

•Specialty Pressure Sensitive Tapes- Laminates-Films, Foils, Papers,