



# DATA SHEET

## PRESSURE SENSITIVE TAPES Tape Products Engineered to your Specifications

PRODUCT: 243-L LEAD

CONSTRUCTION: Backing: 0.003" Lead Foil  
Adhesive: Acrylic  
Interliner: Polycoated Paper Liner

FEATURES / BENEFITS: Highly conformable to both irregular and curved surfaces.

Aggressive acrylic PS adhesive is designed to offer excellent quick stick and ultimate adhesion.

Liner allows tape to be die cut into shapes.

APPLICATION: MASKING SEALING  
Electroplating Radioactive canisters  
X-ray plates Thermopane windows  
Chemical milling

SHIELDING DECORATIVE  
Radiation barrier Simulated lead windows

<u>PROPERTY</u>	<u>VALUE</u>	<u>TEST METHOD</u>
Thickness w/o liner:	0.004 inch +/- 10%	ASTM-D-3652
Peel Strength:	35 oz./inch of width	ASTM-D-1000
Breaking Strength:	10 lbs./inch of width	ASTM-D-1000
Elongation at Break:	15%	ASTM-D-1000
Color:	Natural	
Shelf Life:	1 year when stored under conditions of 70 degrees F. (21 degrees C.) and 50% R.H.	

P/N 477

Rev 1: 04/26/07

*Values are not intended for Engineering Specifications. Before using, user shall determine the suitability of the product for his intended use, and user assumes all risk and liability whatsoever in connection therewith.  
Seller assumes no liability beyond the replacement value of material.*

•Manufacturers of Flexible Laminated and Coated Products. Fabrics.

•Electrical and Electronic Shielding and insulation Composites.

•Specialty Pressure Sensitive Tapes- Laminates-Films, Foils, Papers,