



DATA SHEET

PRESSURE SENSITIVE TAPES

Tape Products Engineered to your Specifications

PRODUCT: 602 TAPE

CONSTRUCTION: Backing: 0.002" Silver Metallized Polyester
 Adhesive: Acrylic
 Interliner: Available

FEATURES / BENEFITS: Heavy duty version of 601 tape, when a more durable metallized film is required.

Highly reflective metallized layer allows for easy visual or electronic splice detection and the automatic sorting of parts.

Aggressive acrylic PS adhesive is designed to offer excellent quick stick and ultimate adhesion.

<u>PROPERTY</u>	<u>VALUE</u>	<u>TEST METHOD</u>
Thickness:	0.003 inch +/- 10%	ASTM-D-3652
Peel Strength:	32 oz./inch of width	ASTM-D-1000
Breaking Strength:	40 lbs./inch of width	ASTM-D-1000
Elongation at Break:	100%	ASTM-D-1000
Color:	Silver	
Shelf Life:	1 year when stored under conditions of 70 degrees F. (21 degrees C.) and 50% R.H.	

P/N 488

Rev 1: 04/26/07

Values are not intended for Engineering Specifications. Before using, user shall determine the suitability of the product for his intended use, and user assumes all risk and liability whatsoever in connection therewith. Seller assumes no liability beyond the replacement value of material.

•Manufacturers of Flexible Laminated and Coated Products. Fabrics.

•Electrical and Electronic Shielding and insulation Composites.

•Specialty Pressure Sensitive Tapes- Laminates-Films, Foils, Papers,