



LAMART CORPORATION

Flexible Laminate Solutions

Technical Data

www.lamartcorp.com

800-LAMART9

973-772-6262

PRODUCT ID: SW-100

DESCRIPTION: **CABLESHIELD**
Laminated Tapes Engineered for the Wire and Cable Industry...

CONSTRUCTION: 0.00092" polyester film
0.00025" acrylic pressure sensitive adhesive

APPLICATION: Pressure sensitive binding tape
Moisture barrier tape
No heat required to obtain seal

PROPERTY	VALUE	TEST METHOD
Thickness:	0.0012 inch +/- 10%	ASTM-D-3652
Breaking Strength:	22 lbs./inch of width	ASTM-D-882
Tensile Strength:	16,923 p.s.i.	ASTM-D-882
Elongation at Break:	69 %	ASTM-D-882
Color:	Clear Colors available	
Weight per Square Yard:	1.26 oz./sq.yd. +/- 10%	
Yield:	12.6 sq.yds./lb. +/- 10%	
Peel Strength:	Adhesion to stainless steel 12 oz./inch of width	ASTM-D-1000
Shelf life:	1year when stored under conditions of 70 degrees F (21 degrees C) and 50% RH.	

P/N 61

Date: (Rev.1): 08/17/05

Values are not intended for Engineering Specifications. Before using, user shall determine the suitability of the product for his intended use, and user assumes all risk and liability whatsoever in connection therewith. Seller assumes no liability beyond the replacement value of material.

Automotive . Aerospace . Electronics . Industrial . Medical . Printing and Graphics