



DATA SHEET

CABLESHIELD

Laminated Tapes Engineered for
the Wire and Cable Industry...

PRODUCT: SW-200

CONSTRUCTION: Backing: 0.002" polyester film
Adhesive: Acrylic pressure sensitive

APPLICATION: Pressure sensitive binding tape
Moisture barrier tape
No heat required to obtain seal

<u>PROPERTY</u>	<u>VALUE</u>	<u>TEST METHOD</u>
Film thickness:	0.002" polyester film - nominal	ASTM-D-3652
Adhesive thickness:	0.0003" +/- 0.00005"	
Breaking Strength:	40 lbs./inch of width	ASTM-D-882
Tensile Strength:	19,000 p.s.i.	ASTM-D-882
Elongation at Break:	100%	ASTM-D-882
Color:	Clear Colors available	
Weight per Square Yard:	2.48 oz./sq.yd. +/- 10%	
Yield:	6.5sq.yds./lb. +/- 10%	
Peel Strength:	Adhesion to stainless steel 12 oz./inch of width	ASTM-D-1000
Shelf Life:	1 year when stored under conditions of 70 degrees F. (21 degrees C.) and 50% RH.	

P/N 62 date 07/02/02

*Values are not intended for Engineering Specifications. Before using, user shall determine the suitability of the product for his intended use, and user assumes all risk and liability whatsoever in connection therewith.
Seller assumes no liability beyond the replacement value of material.*

•Manufacturers of Flexible
Laminated and Coated Products.

•Electrical and Electronic Shielding
and insulation Composites.

•Specialty Pressure Sensitive Tapes-
Laminates-Films, Foils, Papers, Fabrics.