



DATA SHEET

CABLESHIELD

Laminated Tapes Engineered for
the Wire and Cable Industry...

PRODUCT: MHS-050-CLEAR

CONSTRUCTION: 0.00048" polyester film
Heat Sealable Polyester Adhesive

<u>PROPERTY</u>	<u>VALUE</u>	<u>TEST METHOD</u>
Thickness:	.005 +/- 10%	ASTM-D-374
Tensile Strength:	26,000 psi min.	ASTM D-882
Elongation MD:	75%	ASTM-D-882
Dielectric Strength:	2.8 Kv	ASTM-D-149
Heat Seal Temperature:	325 degrees F., 5 seconds	
Shelf Life:	1 year when stored under conditions of 70 degrees F. (21 degrees C.) and 50% RH.	

P/N 6929 (clear)

date 03/27/96

*Values are not intended for Engineering Specifications. Before using, user shall determine the suitability of the product for his intended use, and user assumes all risk and liability whatsoever in connection therewith.
Seller assumes no liability beyond the replacement value of material.*

*•Manufacturers of Flexible
Laminated and Coated Products.*

*•Electrical and Electronic Shielding
and insulation Composites.*

*•Specialty Pressure Sensitive Tapes-
Laminates-Films, Foils, Papers, Fabrics.*